

PANORAMA P SERIES (NON-ABSORBENT INK)

GENERAL DESCRIPTION

PANORAMA-P series ink is formulated for using on non-absorbent substrates, especially al-foils, plastics, synthetic paper, and is drying by oxidation, but contains no aggressive solvents.

FEATURES

- Quick drying time, 100% solid system(solvent free)
- Excellent adhesion to a wide range of plastics and foils
- Excellent Lithographic performance
- High flexibility, good scuff and anti-scratch
- High density, sharp dot reproduction

SPECIFICATIONS

ITEM	PANORAMA-P			
	MAGENTA	YELLOW	CYAN	BLACK
T.V	11.0	10.5	11.5	12.0
D.M	35.0	38.0	36.0	36.0
DENSITY	1.81	1.62	2.27	
DRYING	3.5	3.0	3.0	3.0
NON-SKINNING	5 ↓	5 ↓	5 ↓	5 ↓

TEST METHOD

- T.V : Ink-O-Meter 400RPM 60 sec/32°C (± 0.5)
- D.M : Spread-O-Meter 60 sec/25°C
- Density : Gretag Macbeth D-196 Density-meter
- Drying(Hr) : Drum type drying tester on coated paper
- Non-Skinning(Hr) : Drying on the glass at 25°C

NOTE

- Don't mix with other type of inks.
- Please pay attention not to keep ink on the machine over 2 hours, ink can be dried.
- According to various substrates, please adjust drying by adding suitable amount of drier into ink.



A.S. INK & CHEMICAL CO., LTD

Room No. 405 Woolim E-Biz Center, 16, Yangpyeongdong 3-Ga, Youngdeungpo-Ku, Seoul, Korea.

PHONE: 82-2-2164-8220/4 FAX: 82-2-2164-8225 E-MAIL: asink@asink.com